

DUPAGRO BREAK OUT UNITS



Our Break out units are designed for fast and easy operation when making up or breaking out pipe and tool joints. The units are equipped with Drill Pipe Wrenches to provide the greatest strength while minimizing marks on pipe surfaces. The heat-treated Special Chains on these tools are easily adjusted by adding or reducing the chain sections. The smallest ones have a manual operated hydraulic system, the larger size have their own hydraulic power pack.

2344



6184



8184



DUPAGRO BREAK OUT UNITS

TYPE	2344	6184	8184	11800	118
Maximum Nm	16000	32000	65000	121000	120000
Minimum OD mm	66	108	117	101	101

TYPE	2344	6184	8184	11800	118
Max. Nm	16000	32000	65000	121000	120000
Hydraulic pump	Manual	Manual	Manual or Petrol engine	Petrol engine	Petrol engine 5kW
Hydraulic pressure	105/140	95/140	145/195	135/175	200
Oil tank ltr.	2	7	30	30	30
Hydraulic hoses 5mtr	2	2	2	2	-
Heavy Duty pipe tong /w std. chain	2	2	2	2	1 vise & 1 tong
Dry weight kg*	85	115	275	600	900
Overall size*	80x50x35	120x60x60	120x80x75	130x80x75	180x170x150

Self contained units include:

Transport & service frame, complete hydraulic system, 5mtr hoses with snap couplings

Hydraulic oil type 38 or 48 is NOT included.

* weight and sizes are indicative.

CHAIN OPTIONS

TYPE	CHAIN	OD	OD
2344	07D	*2-5/8" - 3-1/2"	66-90mm
2344	09D	3-5/8" - 4-3/8"	92-111mm
2344	11D	4-1/2" - 5"	114-127mm

*4 Diamond Point or 4 Knurled Inserts, are required to grip 2-1/8" - 3-1/2" O.D with chain 05D

TYPE	CHAIN	OD	OD
6184	09D7	*4-1/4" - 4-3/4"	108-120mm
6184	11D7	4-3/4" - 5-3/4"	120-146mm
6184	13D7	5-3/4" - 6-5/8"	146-168mm

*4 Diamond Point or 4 Knurled Inserts, are required to grip 4-1/4" - 4-3/4" O.D

TYPE	CHAIN	OD	OD
8184	45-09D	4-5/8" - 5-3/4"	117-146mm
8184	45-11D	5-7/8" - 7"	149-177mm
8184	45-13D	7" - 8-1/8"	177-206mm
8184	45-15D	8-1/8" - 9-1/4"	206-235mm
8184	45-17D	9-1/4" - 10-3/8"	235-263mm

TYPE	CHAIN	OD	OD
11800	45-25T	4-5/8" - 5-3/4"	101-304mm
11800	45-33T	5-7/8" - 7"	202-457mm